



Inspection

Weeks Construction & Wrecking

Project: - Inspections Project
6305 Carpinteria Ave
Carpinteria, California 93013

Fixed Ladders #1

TYPE: Health and Safety

TRADE: Health and Safety

STATUS: Open

SPEC SECTION:

LOCATION:

DESCRIPTION:

This checklist covers regulations issued by the U.S. Department of Labor, Occupational Safety and Health Administration (OSHA) under the general industry standard 29 CFR 1910.27. It applies to fixed ladders between the pitch range of 60E to 90E of the horizontal. Fixed ladders in the range of 75E to 90E of the horizontal are preferred. The regulations cited apply only to private employers and their employees, unless adopted by a State agency and applied to other groups such as public employees. This checklist does not address fixed ladders with cages, baskets, wells, hatch covers, landing platforms, or ladders exceeding 20 feet in height (see 29 CFR 1910.27). It also does not address fixed ladders associated with construction sites (see 29 CFR 1926.1051 and 1926.1053). Consult the OSHA regulations for requirements in these situations.

ATTACHMENTS:

INSPECTION DETAILS

INSPECTION DATE: 2/11/2016

INSPECTOR:

RESPONSIBLE CONTRACTOR:

POINT OF CONTACT:



Inspection

Fixed Ladders

1.1	1. Is the distance between rungs 12 inches or less and uniform throughout the length of the ladder? [29 CFR 1910.27(b)(1)(ii)]	<input type="checkbox"/> Y	<input type="checkbox"/> N	<input type="checkbox"/> N/A
Activity: 0 Comments, 0 Attachments, 0 Photos, 0 Status Changes				
1.2	2. Is the minimum clear length of rungs or cleats at least 16 inches? [29 CFR 1910.27(b)(1)(iii)]	<input type="checkbox"/> Y	<input type="checkbox"/> N	<input type="checkbox"/> N/A
Activity: 0 Comments, 0 Attachments, 0 Photos, 0 Status Changes				
1.3	3. Are the rungs, cleats, and steps free of splinters, sharp edges, burrs, or other projections that are hazards? [29 CFR 1910.27(b)(1)(iv)]	<input type="checkbox"/> Y	<input type="checkbox"/> N	<input type="checkbox"/> N/A
Activity: 0 Comments, 0 Attachments, 0 Photos, 0 Status Changes				
1.4	4. Are the rungs of ladders designed so that the foot cannot slip off the end? [29 CFR 1910.27(b)(1)(v)]	<input type="checkbox"/> Y	<input type="checkbox"/> N	<input type="checkbox"/> N/A
Activity: 0 Comments, 0 Attachments, 0 Photos, 0 Status Changes				
1.5	5. Are the rungs of metal ladders at least three-fourths of one inch in diameter? [29 CFR 1910.27(b)(1)(i)]	<input type="checkbox"/> Y	<input type="checkbox"/> N	<input type="checkbox"/> N/A
Activity: 0 Comments, 0 Attachments, 0 Photos, 0 Status Changes				
1.6	6. Are the rungs of wood ladders at least 1-1/8 inches in diameter? [29 CFR 1910.27(b)(1)(i)]	<input type="checkbox"/> Y	<input type="checkbox"/> N	<input type="checkbox"/> N/A
Activity: 0 Comments, 0 Attachments, 0 Photos, 0 Status Changes				
1.7	7. Do siderails that might be used as a climbing aid provide adequate gripping surface without sharp edges, splinters, or burrs? [29 CFR 1910.27(b)(2)]	<input type="checkbox"/> Y	<input type="checkbox"/> N	<input type="checkbox"/> N/A
Activity: 0 Comments, 0 Attachments, 0 Photos, 0 Status Changes				
1.8	8. Are metal ladders painted or treated to protect them from corrosion and rusting when location demands? [29 CFR 1910.27(b)(7)(i)]	<input type="checkbox"/> Y	<input type="checkbox"/> N	<input type="checkbox"/> N/A
Activity: 0 Comments, 0 Attachments, 0 Photos, 0 Status Changes				
1.9	9. Are wood ladders treated with a nonirritating preservative when used under conditions that may cause decay? [29 CFR 1910.27(b)(7)(ii)]	<input type="checkbox"/> Y	<input type="checkbox"/> N	<input type="checkbox"/> N/A
Activity: 0 Comments, 0 Attachments, 0 Photos, 0 Status Changes				



Inspection

1.10	10. Is the perpendicular distance from the center line of the rungs to the nearest permanent object on the climbing side of the ladder 36 inches for a pitch of 76o and 30 inches for a pitch of 90o? [29 CFR 1910.27(c)(1)]	<input type="checkbox"/> Y	<input type="checkbox"/> N	<input type="checkbox"/> N/A
Activity: 0 Comments, 0 Attachments, 0 Photos, 0 Status Changes				
1.11	11. Is the distance from the center line of the rung, cleat, or step to the nearest permanent object behind the ladder at least 7 inches? [29 CFR 1910.27(c)(4)]	<input type="checkbox"/> Y	<input type="checkbox"/> N	<input type="checkbox"/> N/A
Activity: 0 Comments, 0 Attachments, 0 Photos, 0 Status Changes				
1.12	12. Is the distance from the center line of the grab bar to the nearest permanent object behind the grab bar at least 4 inches? [29 CFR 1910.27(c)(5)]	<input type="checkbox"/> Y	<input type="checkbox"/> N	<input type="checkbox"/> N/A
Activity: 0 Comments, 0 Attachments, 0 Photos, 0 Status Changes				
1.13	13. Is the step-across distance from the nearest edge of the ladder to the nearest edge of the equipment or structure not more than 12 inches and not less than 2-1/2 inches? [29 CFR 1910.27(c)(6)]	<input type="checkbox"/> Y	<input type="checkbox"/> N	<input type="checkbox"/> N/A
Activity: 0 Comments, 0 Attachments, 0 Photos, 0 Status Changes				
1.14	14. Are the siderails of ladders extended at least 3-1/2 feet above the landing? [29 CFR 1910.27(d)(3)]	<input type="checkbox"/> Y	<input type="checkbox"/> N	<input type="checkbox"/> N/A
Activity: 0 Comments, 0 Attachments, 0 Photos, 0 Status Changes				
1.15	15. Are all ladders inspected regularly and maintained in a safe condition? [29 CFR 1910.27(f)]	<input type="checkbox"/> Y	<input type="checkbox"/> N	<input type="checkbox"/> N/A
Activity: 0 Comments, 0 Attachments, 0 Photos, 0 Status Changes				

Summary: 0 0 0

Inspection Summary: 0 0 0